

HARWIN

INDESS


PC/104 and PC/104 Plus



INDUSTRY STANDARD FOR EMBEDDED PCS

Stackthrough


Non-Stackthrough



The PC/104 and PC/104 Plus connection system is a popular industry standard used for embedded PC applications, designed for stacked boards with a common bus system.

- Using just the 2.54mm pitch PC/104 32+32-contact connector, an 8-bit bus is achieved (J1).
- Adding the 20+20-contact connector increases this to a 16-bit bus (J1 + J2).
- With the inclusion of the 2mm pitch PC/104 Plus connector (4 rows x 30 contact), the system becomes PCI Bus compatible (J1, J2, J3).


STACKTHROUGH CONNECTION



The Harwin PC/104 connectors are based on a tuning fork contact, which allows stamped connections with tails just like male Pin Headers. The terminations of the upper connector in the stack can therefore plug into the connector below it.

- PC/104 (2.54mm pitch), 32+32 contacts = [M20-6103245](#)
- PC/104 (2.54mm pitch), 20+20 contacts = [M20-6102045](#)
- PC/104 Plus (2.00mm pitch), 4 x 30 contacts = [M22-6003005](#)


NON-STACKTHROUGH CONNECTION



To complete the bottom layer of the PC Bus, a non-stackthrough connector is required. These connectors have sort tails, designed for soldering to a standard 1.6mm thick PCB.

- PC/104 (2.54mm pitch), 32+32 contacts = [M20-6113245](#)
- PC/104 (2.54mm pitch), 20+20 contacts = [M20-6112045](#)
- PC/104 Plus (2.00mm pitch), 4 x 30 contacts = [M22-6013005](#)

PRESS-FIT CONNECTION – NO SOLDER REQUIRED



PC/104 connectors (2.54mm pitch) have the alternative option of press-fit terminations. This removes the requirement for soldering, by forming a gas-tight joint with a plated-through hole on the PCB. This option is available on both the stackthrough and non-stackthrough connectors:

- Stackthrough, 32+32 contacts = [M20-6153205](#)
- Non-Stackthrough, 32+32 contacts = [M20-6163205](#)
- Stackthrough, 20+20 contacts = [M20-6152005](#)
- Non-Stackthrough, 20+20 contacts = [M20-6162005](#)

ACCESSORIES



As part of the PC/104 range, Harwin also offer:

- PC/104 Plus Shroud for use with stackthrough terminations (assembles to underside of PCB) – [M22-6043098](#)
- Male/Female Spacer, 15.24mm (0.6") body length, for PC/104 board stacking – [R6104-02](#)

ELECTRICAL SPECIFICATIONS

Current Rating	PC/104 Solder Tail = 3A per contact PC/104 Press-Fit = 1A per contact PC/104 Plus = 1A per contact
Contact Resistance	50m Ω max
Insulation Resistance	5,000MΩ min

The full Component Specification for Harwin's PC/104 range is available [to download](#).

MECHANICAL & ENVIRONMENTAL SPECIFICATIONS

Temperature Range	-55°C to +105°C
Durability (mating)	10 mating operations
Durability (Press-fit to PCB)	3 mating operations

All Solder Termination connectors are manufactured using the same housing materials used on Surface Mount connectors, and can therefore withstand the same reflow soldering processes.

MARKETS



The main PCB applications using PC/104 and PC/104 Plus are Embedded PCs. These are well established in applications such as industrial machinery and larger electronics systems.

- Production Equipment
- Communications
- Drives and Controls
- Industrial Monitoring
- Embedded Computing

Learn more about our other ranges



HIGH RELIABILITY
WITH SUPREME
PERFORMANCE



INNOVATIVE
DESIGNS FOR
EASY ASSEMBLY



DEPENDABLE
CONNECTIVITY
ACROSS THE BOARD

Find out more about our full range
of inter-connection solutions at

www.harwin.com

HRI
RANGE

EZi
RANGE

BBi
RANGE

Get Help from a Harwin Expert

Our experts are specialists in their field with many years of experience in their respective roles and industries.

Find an expert that can help you with your enquiry.

[Click Here >>](#)

CAD Models and Evaluation Samples also available at www.harwin.com



Contact Us

Europe, Middle East & Africa

T: +44 (0)23 9231 4545

E: technical@harwin.com

Americas

T: +1 603 893 5376

E: technical-us@harwin.com

Asia Pacific

T: +65 6 779 4909

E: technical-asia@harwin.com

WWW.HARWIN.COM