

Material Declaration for M80-502XXXX

Product Information	
Part Number:	M80-502XX05
Part Description:	Vertical Male Datamate J-Tek
Part Weight (g):	(0.0353 * XX) + 0.636

Process Data	
Peak Reflow (Deg. C)	260°C for 10 sec
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.012 * XX	2%	Copper	7440-50-8
	0.00062 * XX	1%	Tin	7440-31-5
	0.000023 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000037 * XX)g max	Zinc	7440-66-6
	0	(0.000012 * XX)g max	Iron	7439-89-6
Contacts - Plating	0	(0.000006 * XX)g max	Lead	7439-92-1
	0	(0.000062 * XX)g max	Impurities	
	0.00017 * XX	5%	Gold	7440-57-5
	0.00013 * XX	10%	Nickel	7440-02-0
Jackscrews - Stainless Steel	0.233	5%	Iron	7439-89-6
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0.059	2%	Chromium (Metallic)	7440-47-3
	0.00082	0.5%	Sulphur	7704-34-9
	0.0295	2%	Nickel	7440-02-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
	0.00524	0.8%	Copper	7440-50-8
Moulding (total weight)	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
Containing:	(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

Material Declaration for M80-502XXXX

Product Information	
Part Number:	M80-502XX22
Part Description:	Vertical Male Datamate J-Tek
Part Weight (g):	(0.0353 * XX) + 0.636

Process Data	
Peak Reflow (Deg. C)	235°C for 5 seconds
Termination Finish	Tin/Lead over Nickel
RoHS Compliant? (Y/N)	No

Note: RoHS compliant by threshold values, lead intentionally added, not recommended for Lead-Free Soldering.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.012 * XX	2%	Copper	7440-50-8
	0.00062 * XX	1%	Tin	7440-31-5
	0.000023 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000037 * XX)g max	Zinc	7440-66-6
	0	(0.000012 * XX)g max	Iron	7439-89-6
	0	(0.000006 * XX)g max	Lead	7439-92-1
Contacts - Plating	0	(0.000062 * XX)g max	Impurities	
	0.000066 * XX	5%	Gold	7440-57-5
	0.00012 * XX	5%	Tin	7440-31-5
	0.00002 * XX	5%	Lead	7439-92-1
	0.00013 * XX	10%	Nickel	7440-02-0
Jackscrews - Stainless Steel	0.233	5%	Iron	7439-89-6
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0.059	2%	Chromium (Metallic)	7440-47-3
	0.00082	0.5%	Sulphur	7704-34-9
	0.0295	2%	Nickel	7440-02-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
	0.00524	0.8%	Copper	7440-50-8
	Moulding (total weight)	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS
Containing:	(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	


Material Declaration for M80-502XXXX

Product Information	
Part Number:	M80-502XX42
Part Description:	Vertical Male Datamate J-Tek
Part Weight (g):	(0.0352 * XX) + 0.636

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.012 * XX	2%	Copper	7440-50-8
	0.00062 * XX	1%	Tin	7440-31-5
	0.000023 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000037 * XX)g max	Zinc	7440-66-6
	0	(0.000012 * XX)g max	Iron	7439-89-6
Contacts - Plating	0	(0.000006 * XX)g max	Lead	7439-92-1
	0	(0.000062 * XX)g max	Impurities	
	0.000066 * XX	5%	Gold	7440-57-5
	0.00013 * XX	5%	Tin	7440-31-5
	0.00013 * XX	10%	Nickel	7440-02-0
Jackscrews - Stainless Steel	0.233	5%	Iron	7439-89-6
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0.059	2%	Chromium (Metallic)	7440-47-3
	0.00082	0.5%	Sulphur	7704-34-9
	0.0295	2%	Nickel	7440-02-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
	0.00524	0.8%	Copper	7440-50-8
	Moulding (total weight)	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS
Containing:	(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of: 