

Material Declaration for H3155-XX

Product Information	
Part Number:	H3155-01
Part Description:	Sub-Miniature PCB Socket
Part Weight (g):	0.0229

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.0114	2%	Copper	7440-50-8
	0.00764	1%	Zinc	7440-66-6
	0.000588	0.5%	Lead	7439-92-1
	0	0.000059g max	Iron (impurity only)	7439-89-6
	0	0.000059g max	Tin (impurity only)	7440-31-5
	0	0.000059g max	Nickel (impurity only)	7440-02-0
	0	0.00001g max	Aluminium (impurity only)	7429-90-5
Contact Shell - Plating	0	0.000039g max	Other Impurities	
	0.000696	5%	Tin	7440-31-5
	0.000424	10%	Nickel	7440-02-0
Contact Clip - Beryllium Copper	0.00207	1%	Copper	7440-50-8
	0.00004	0.5%	Beryllium	7440-41-7
	0	0.000006g max	Nickel (impurity only)	7440-02-0
	0	0.000006g max	Cobalt (impurity only)	7440-48-4
	0	0.000004g max	Iron (impurity only)	7439-89-6
	0	0.000004g max	Aluminium (impurity only)	7429-90-5
	0	0.000004g max	Silicon (impurity only)	7440-21-3
	0	0.000011g max	Other Impurities	
Contact Clip - Plating	0.000006	5%	Gold	7440-57-5
	0.000057	10%	Nickel	7440-02-0

Material Declaration for H3155-XX

Product Information	
Part Number:	H3155-05
Part Description:	Sub-Miniature PCB Socket
Part Weight (g):	0.0223

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.0114	2%	Copper	7440-50-8
	0.00764	1%	Zinc	7440-66-6
	0.000588	0.5%	Lead	7439-92-1
	0	0.000059g max	Iron (impurity only)	7439-89-6
	0	0.000059g max	Tin (impurity only)	7440-31-5
	0	0.000059g max	Nickel (impurity only)	7440-02-0
	0	0.00001g max	Aluminium (impurity only)	7429-90-5
Contact Shell - Plating	0	0.000039g max	Other Impurities	
	0.000046	5%	Gold	7440-57-5
	0.000424	10%	Nickel	7440-02-0
Contact Clip - Beryllium Copper	0.00207	1%	Copper	7440-50-8
	0.00004	0.5%	Beryllium	7440-41-7
	0	0.000006g max	Nickel (impurity only)	7440-02-0
	0	0.000006g max	Cobalt (impurity only)	7440-48-4
	0	0.000004g max	Iron (impurity only)	7439-89-6
	0	0.000004g max	Aluminium (impurity only)	7429-90-5
	0	0.000004g max	Silicon (impurity only)	7440-21-3
	0	0.000011g max	Other Impurities	
Contact Clip - Plating	0.000006	5%	Gold	7440-57-5
	0.000057	10%	Nickel	7440-02-0


Material Declaration for H3155-XX

Product Information	
Part Number:	H3155-46
Part Description:	Sub-Miniature PCB Socket
Part Weight (g):	0.0231

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.0114	2%	Copper	7440-50-8
	0.00764	1%	Zinc	7440-66-6
	0.000588	0.5%	Lead	7439-92-1
	0	0.000059g max	Iron (impurity only)	7439-89-6
	0	0.000059g max	Tin (impurity only)	7440-31-5
	0	0.000059g max	Nickel (impurity only)	7440-02-0
Contact Shell - Plating	0	0.00001g max	Aluminium (impurity only)	7429-90-5
	0	0.000039g max	Other Impurities	
	0.000696	5%	Tin	7440-31-5
	0.000424	10%	Nickel	7440-02-0
Contact Clip - Beryllium Copper	0.00207	1%	Copper	7440-50-8
	0.00004	0.5%	Beryllium	7440-41-7
	0	0.000006g max	Nickel (impurity only)	7440-02-0
	0	0.000006g max	Cobalt (impurity only)	7440-48-4
	0	0.000004g max	Iron (impurity only)	7439-89-6
	0	0.000004g max	Aluminium (impurity only)	7429-90-5
	0	0.000004g max	Silicon (impurity only)	7440-21-3
	0	0.000011g max	Other Impurities	
Contact Clip - Plating	0.000139	5%	Tin	7440-31-5
	0.000136	10%	Nickel	7440-02-0

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
 Compliance Specialist
 ComplianceTeam@harwin.co.uk

On behalf of:

