

Material Composition for M50-330XX42

Product Information	
Part Number:	M50-330XX42
Part Description:	1.27mm pitch IDC Socket
Part Weight (g):	(0.0312 * XX) + 0.102

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	0.0142 * XX	5%	Copper	7440-50-8
	0.00095 * XX	1%	Tin	7440-31-5
	0.000028 * XX	0.5%	Phosphorus	7723-14-0
	0	(0.00003 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000016 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000008 * XX)g max	Lead (impurity only)	7439-92-1
Contact - Plating	0	(0.000076 * XX)g max	Other Impurities	
	0.000414 * XX	10%	Nickel	7440-02-0
	0.000002 * XX	30%	Gold	7440-57-5
	0.000118 * XX	10%	Tin	7440-31-5
Mouldings (total weight)	(0.0155 * XX) + 0.102	5%	30% GF PBT	
Containing:	(0.00775 * XX) + 0.051	5%	PBT	30965-26-5
	(0.00465 * XX) + 0.0306	5%	30% Glass Fibre	65997-17-3
	(0.000775 * XX) + 0.0051	5%	Antimony Trioxide	1309-64-4
	(0.00233 * XX) + 0.0153	5%	Other Brominated Flame Retardants [ISO 1043-4 Code No: FR(17)]	

Prepared by:



Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

