

Material Composition for M40-302XX46, M40-302XX46R


Product Information	
Part Number:	M40-302XX46
Part Description:	1.00mm pitch Header
Part Weight (g):	(0.0219 * XX) + 0.0881

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating subject to 1,000ppm max Lead impurity.

Note: Weights for M40-302XX46R are identical.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	0.00437 * XX	5%	Copper	7440-50-8
	0.00023 * XX	1%	Tin	7440-31-5
	0.000009 * XX	0.50%	Phosphorus	7723-14-0
	0	(0.000009 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000009 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000005 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000001 * XX)g max	Lead (impurity only)	7439-92-1
Contact - Plating	0	(0.000009 * XX)g max	Other Impurities	
	0.000135 * XX	10%	Nickel	7440-02-0
	0.000166 * XX	10%	Tin	7440-31-5
Retainers - Phosphor Bronze	0.0104	5%	Copper	7440-50-8
	0.00055	1%	Tin	7440-31-5
	0.000022	0.50%	Phosphorus	7723-14-0
	0	0.000022g max	Nickel (impurity only)	7440-02-0
	0	0.000022g max	Zinc (impurity only)	7440-66-6
	0	0.00001g max	Iron (impurity only)	7439-89-6
	0	0.000002g max	Lead (impurity only)	7439-92-1
Retainers - Plating	0	0.000022g max	Other Impurities	
	0.000282	10%	Nickel	7440-02-0
	0.000348	10%	Tin	7440-31-5
Moulding (total weight)	(0.0121 * XX) + 0.074	6%	33% GF LCP	
Containing:	(0.0811 * XX) + 0.0496	6%	Liquid Crystal Polymer	
	(0.00399 * XX) + 0.0244	6%	Glass Fibre	65997-17-3
Does not contain:			Other Brominated Flame Retardants	
			Antimony	
Pick and Place cap (total weight)	0.00251	6%	33% GF LCP	
Containing:	0.00168	6%	Liquid Crystal Polymer	
	0.000828	6%	Glass Fibre	65997-17-3
Does not contain:			Other Brominated Flame Retardants	
			Antimony	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

