

Material Declaration for H3490-XX

Product Information	
Part Number:	H3490-01
Part Description:	1mm PC Board Socket
Part Weight (g):	0.554

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.299	2%	Copper	7440-50-8
	0.0155	0.5%	Lead	7439-92-1
	0.201	1%	Zinc	7440-66-6
	0	0.00155g max	Iron (impurity only)	7439-89-6
	0	0.00155g max	Tin (impurity only)	7440-31-5
	0	0.00155g max	Nickel (impurity only)	7440-02-0
Contact Shell - Plating	0	0.000228g max	Aluminium (impurity only)	7429-90-5
	0	0.00103g max	Other Impurities	
	0.00418	10%	Nickel	7440-02-0
	0.00687	10%	Tin	7440-31-5
Contact Clip - Beryllium Copper	0.0261	2%	Copper	7440-50-8
	0.000507	1%	Beryllium	7440-41-7
	0	0.00008g max	Nickel (impurity only)	7440-02-0
	0	0.00008g max	Cobalt (impurity only)	7440-48-4
	0	0.000053g max	Iron (impurity only)	7439-89-6
	0	0.000053g max	Aluminium (impurity only)	7429-90-5
	0	0.000053g max	Silicon (impurity only)	7440-21-3
	0	0.000133g max	Other Impurities	
	0.000389	10%	Nickel	7440-02-0
0.000006	5%	Gold	7440-57-5	
0				

Material Declaration for H3490-XX

Product Information	
Part Number:	H3490-05
Part Description:	1mm PC Board Socket
Part Weight (g):	0.547

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.299	2%	Copper	7440-50-8
	0.0155	0.5%	Lead	7439-92-1
	0.201	1%	Zinc	7440-66-6
	0	0.00155g max	Iron (impurity only)	7439-89-6
	0	0.00155g max	Tin (impurity only)	7440-31-5
	0	0.00155g max	Nickel (impurity only)	7440-02-0
	0	0.000228g max	Aluminium (impurity only)	7429-90-5
Contact Shell - Plating	0	0.00103g max	Other Impurities	
	0.00418	10%	Nickel	7440-02-0
	0.000453	5%	Gold	7440-57-5
Contact Clip - Beryllium Copper				
	0.0261	2%	Copper	7440-50-8
	0.000507	1%	Beryllium	7440-41-7
	0	0.00008g max	Nickel (impurity only)	7440-02-0
	0	0.00008g max	Cobalt (impurity only)	7440-48-4
	0	0.000053g max	Iron (impurity only)	7439-89-6
	0	0.000053g max	Aluminium (impurity only)	7429-90-5
	0	0.000053g max	Silicon (impurity only)	7440-21-3
Contact Clip - Plating	0	0.000133g max	Other Impurities	
	0.000389	10%	Nickel	7440-02-0
	0.000006	5%	Gold	7440-57-5

Material Declaration for H3490-XX

Product Information	
Part Number:	H3490-46
Part Description:	1mm PC Board Socket
Part Weight (g):	0.555

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.299	2%	Copper	7440-50-8
	0.0155	0.5%	Lead	7439-92-1
	0.201	1%	Zinc	7440-66-6
	0	0.00155g max	Iron (impurity only)	7439-89-6
	0	0.00155g max	Tin (impurity only)	7440-31-5
	0	0.00155g max	Nickel (impurity only)	7440-02-0
	0	0.000228g max	Aluminium (impurity only)	7429-90-5
Contact Shell - Plating	0	0.00103g max	Other Impurities	
	0.00418	10%	Nickel	7440-02-0
	0.00687	10%	Tin	7440-31-5
Contact Clip - Beryllium Copper	0.0261	2%	Copper	7440-50-8
	0.000507	1%	Beryllium	7440-41-7
	0	0.00008g max	Nickel (impurity only)	7440-02-0
	0	0.00008g max	Cobalt (impurity only)	7440-48-4
	0	0.000053g max	Iron (impurity only)	7439-89-6
	0	0.000053g max	Aluminium (impurity only)	7429-90-5
	0	0.000053g max	Silicon (impurity only)	7440-21-3
	0	0.000133g max	Other Impurities	
Contact Clip - Plating	0.000389	10%	Nickel	7440-02-0
	0.000959	10%	Tin	7440-31-5

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET
 Compliance Specialist
 ComplianceTeam@harwin.co.uk

On behalf of:

