

Material Declaration for M80-414XX98

Product Information	
Part Number:	M80-414XX98
Part Description:	Female T-Contact Housing
Part Weight (g):	(0.0385 * XX) + 0.733

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Jackscrew Circlips - Stainless Steel	0.0164	10%	Iron	7439-89-6
	0.0033	4%	Chromium (Metallic)	7440-47-3
	0.0002	4%	Nickel	7440-02-0
	0.000078	0.8%	Copper	7440-50-8
	0.000004	0.5%	Sulphur	7704-34-9
	0	0.000078g max	Carbon (impurity only)	7440-44-0
	0	0.0002g max	Silicon (impurity only)	7440-21-3
	0	0.0003g max	Manganese (impurity only)	7439-96-5
	0	0.000008g max	Phosphorus (impurity only)	7723-14-0
	0	0.00021g max	Molybdenum (impurity only)	7439-98-7
Jackscrew Bolts - Stainless Steel	0.405	10%	Iron	7439-89-6
	0.1	4%	Chromium (Metallic)	7440-47-3
	0.0501	4%	Nickel	7440-02-0
	0.0039	0.8%	Copper	7440-50-8
	0.00139	0.5%	Sulphur	7704-34-9
	0	0.000668g max	Carbon (impurity only)	7440-44-0
	0	0.00557g max	Silicon (impurity only)	7440-21-3
	0	0.0111g max	Manganese (impurity only)	7439-96-5
	0	0.000334g max	Phosphorus (impurity only)	7723-14-0
	0	0.00557g max	Molybdenum (impurity only)	7439-98-7
	0	0.00111g max	Niobium (impurity only)	7440-03-1
	0	0.000556g max	Titanium (impurity only)	7440-32-6
Moulding (total weight)	(0.0385 * XX) + 0.153	10%	30% Glass-Filled PPS	
Containing:	(0.027 * XX) + 0.107	10%	PPS	26125-40-6
	(0.0116 * XX) + 0.0459	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET
 Compliance Specialist
 ComplianceTeam@harwin.co.uk

