


## Material Composition for M300-3250396M2

Product Information	
Part Number:	M300-3250396M2
Part Description:	3mm M300 Male Crimp Hsg
Part Weight (g):	1.404

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Jackscrews - Stainless Steel	0.383	5%	Iron	7439-89-6
	0.0969	2%	Chromium (Metallic)	7440-47-3
	0.0485	2%	Nickel	7440-02-0
	0.00862	0.8%	Copper	7440-50-8
	0.00135	0.5%	Sulphur	7704-34-9
	0	0.00043g max	Carbon (impurity only)	7440-44-0
	0	0.00539g max	Silicon (impurity only)	7440-21-3
	0	0.0108g max	Manganese (impurity only)	7439-96-5
	0	0.000242g max	Phosphorus (impurity only)	7723-14-0
	0	0.00323g max	Molybdenum (impurity only)	7439-98-7
	0	0.000592g max	Nitrogen (impurity only)	7727-37-9
Moulding (total weight)	0.866	5%	30% GF Nylon 4T	
Containing:	0.485	5%	Nylon 4T	103945-40-0
	0.26	5%	30% Glass Fibre	65997-17-3
	0.108	5%	Organic phosphorus compound	-
	0.013	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET  
 Compliance Consultant  
 complianceteam@harwin.com

On behalf of:

