


Material Composition for M55-610XX42R

Product Information	
Part Number:	M55-600XX42R
Part Description:	1.27mm pitch Socket
Part Weight (g):	(0.036 * XX) + 0.18

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	0.0192 * XX	5%	Copper	7440-50-8
	0.00129 * XX	1%	Tin	7440-31-5
	0.000039 * XX	0.5%	Phosphorus	7723-14-0
	0	(0.000041 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000021 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000011 * XX)g max	Lead (impurity only)	7439-92-1
Contact - Plating	0	(0.000103 * XX)g max	Other Impurities	
	0.000393 * XX	10%	Nickel	7440-02-0
	0.000056 * XX	10%	Tin	7440-31-5
	0.00003 * XX	10%	Gold	7440-57-5
Retainers - Brass	0.028	5%	Copper	7440-50-8
	0.012	1%	Zinc	7440-66-6
	0	0.000008g max	Aluminium (impurity only)	7429-90-5
	0	0.00012g max	Nickel (impurity only)	7440-02-0
	0	0.00004g max	Tin (impurity only)	7440-31-5
	0	0.00002g max	Iron (impurity only)	7439-89-6
	0	0.000028g max	Lead (impurity only)	7439-92-1
	0	0.00004g max	Other Impurities	
	Retainers - Plating	0.000544	10%	Nickel
0.00112		10%	Tin	7440-31-5
Moulding (total weight)	(0.015 * XX) + 0.138	6%	33% GF LCP	
	Containing:	(0.0101 * XX) + 0.0925	6%	Liquid Crystal Polymer
Does not contain:	(0.00495 * XX) + 0.0455	6%	Glass Fibre	65997-17-3
			Other Brominated Flame Retardants	
			Antimony	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of: 