

Material Declaration for M80-868XXXX

Product Information	
Part Number:	M80-868XX05
Part Description:	2mm Horizontal Datamate
Part Weight (g):	(0.045 * XX) + 0.0885

Process Data	
Peak Reflow (Deg. C)	235°C for 5 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	No

Note: RoHS compliant by threshold values, Lead intentionally added, not recommended for Lead-Free soldering.

2 hold-down straps used per connector

Product Information	
Part Number:	M80-0030006
Part Description:	Hold-down strap
Part Weight (g):	0.0764

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0208 * XX	2%	Copper	7440-50-8
	0.0011 * XX	1%	Tin	7440-31-5
	0.000042 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000066 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000022 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000011 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.00011 * XX)g max	Other Impurities	
	0.000289 * XX	5%	Gold	7440-57-5
	0.000226 * XX	10%	Nickel	7440-02-0
Moulding (total weight) Containing:	(0.0225 * XX) + 0.0885	5%	30% GF PBT	
	(0.0113 * XX) + 0.0443	5%	PBT	30965-26-5
	(0.00675 * XX) + 0.0266	5%	30% Glass Fibre	65997-17-3
	(0.00113 * XX) + 0.00443	5%	Antimony Trioxide	1309-64-4
	(0.00338 * XX) + 0.0133	5%	Other Brominated Flame Retardants [ISO 1043-4 Code No: FR(17)]	

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Brass	0.0467	2%	Copper	7440-50-8
	0.0274	2%	Zinc	7440-66-6
	0	0.000074g max	Lead (impurity only)	7439-92-1
	0	0.000074g max	Iron (impurity only)	7439-89-6
	0	0.000074g max	Tin (impurity only)	7440-31-5
	0	0.000223g max	Nickel (impurity only)	7440-02-0
	0	0.000037g max	Aluminium (impurity only)	7429-90-5
	0	0.000074g max	Other Impurities	
Plating	0.00129	5%	Tin	7440-31-5
	0.00105	10%	Nickel	7440-02-0

Material Declaration for M80-868XXXX

Product Information	
Part Number:	M80-868XX22
Part Description:	2mm Horizontal Datamate
Part Weight (g):	(0.0448 * XX) + 0.0885

Process Data	
Peak Reflow (Deg. C)	235°C for 5 seconds
Termination Finish	Tin/Lead over Nickel
RoHS Compliant? (Y/N)	No

Note: RoHS compliant by threshold values, Lead intentionally added, not recommended for Lead-Free soldering.


2 hold-down straps used per connector

Product Information	
Part Number:	M80-0030006
Part Description:	Hold-down strap
Part Weight (g):	0.0764

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0207 * XX	2%	Copper	7440-50-8
	0.0011 * XX	1%	Tin	7440-31-5
	0.000042 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000066 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000022 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000011 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.00011 * XX)g max	Other Impurities	
	0.000066 * XX	5%	Gold	7440-57-5
	0.000172 * XX	5%	Tin	7440-31-5
	0.00003 * XX	5%	Lead	7439-92-1
Moulding (total weight) Containing:	0.000226 * XX	10%	Nickel	7440-02-0
	(0.0225 * XX) + 0.0885	5%	30% GF PBT	
	(0.0113 * XX) + 0.0443	5%	PBT	30965-26-5
	(0.00675 * XX) + 0.0266	5%	30% Glass Fibre	65997-17-3
	(0.00113 * XX) + 0.00443	5%	Antimony Trioxide	1309-64-4
	(0.00338 * XX) + 0.0133	5%	Other Brominated Flame Retardants [ISO 1043-4 Code No: FR(17)]	

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #	
Brass	0.0467	2%	Copper	7440-50-8	
	0.0274	2%	Zinc	7440-66-6	
	0	0.000074g max	Lead (impurity only)	7439-92-1	
	0	0.000074g max	Iron (impurity only)	7439-89-6	
	0	0.000074g max	Tin (impurity only)	7440-31-5	
	0	0.000223g max	Nickel (impurity only)	7440-02-0	
	0	0.000037g max	Aluminium (impurity only)	7429-90-5	
	0	0.000074g max	Other Impurities		
	Plating	0.00129	5%	Tin	7440-31-5
		0.00105	10%	Nickel	7440-02-0

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

