

Material Composition for M50-303XX42

Product Information	
Part Number:	M50-303XX42
Part Description:	1.27mm pitch Socket
Part Weight (g):	(0.0206 * XX) +0.00518

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	0.00976 * XX	5%	Copper	7440-50-8
	0.000652 * XX	1%	Tin	7440-31-5
	0.00002 * XX	0.5%	Phosphorus	7723-14-0
	0	(0.000021 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.00001 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000002 * XX)g max	Lead (impurity only)	7439-92-1
Contact - Plating	0	(0.000052 * XX)g max	Other Impurities	
	0.0002 * XX	10%	Nickel	7440-02-0
	0.0001 * XX	20%	Tin	7440-31-5
	0.000004 * XX	30%	Gold	7440-57-5
Moulding (total weight)	(0.00991 * XX) + 0.00518	6%	33% GF Nylon 9T	
Containing:	(0.00426 * XX) + 0.00223	6%	Nylon 9T	169284-22-4
	(0.00327 * XX) + 0.00171	6%	Glass Fibre	65997-17-3
	(0.00208 * XX) + 0.00109	6%	Bromopolystyrene	88497-56-7
	(0.000297 * XX) + 0.000155	4%	Additives (such as Heat stabilizer)	
Does not contain:			Antimony	

Prepared by:



Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
leadfree@harwin.co.uk

On behalf of:

