

Material Declaration for M80-828XXXXP

Product Information	
Part Number:	M80-828XX22P
Part Description:	2mm pitch Vert Datamate
Part Weight (g):	(0.0368 * XX) + 0.205

Process Data	
Peak Reflow (Deg. C)	235°C for 5 seconds
Termination Finish	Tin/Lead over Nickel
RoHS Compliant? (Y/N)	No

Note: RoHS compliant by threshold values, lead intentionally added, not recommended for Lead-Free Soldering.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0132 * XX	2%	Copper	7440-50-8
	0.000696 * XX	1%	Tin	7440-31-5
	0.000026 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000042 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000014 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000007 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.00007 * XX)g max	Other Impurities	
	0.000066 * XX	5%	Gold	7440-57-5
	0.000118 * XX	5%	Tin	7440-31-5
	0.00002 * XX	5%	Lead	7439-92-1
Latches - Beryllium Copper	0.000147 * XX	10%	Nickel	7440-02-0
	0.0965	2%	Copper	7440-50-8
	0.00167	0.2%	Beryllium	7440-41-7
	0	0.000294g max	Nickel (impurity only)	7440-02-0
	0	0.000294g max	Cobalt (impurity only)	7440-48-4
Latches - Plating	0	0.000196g max	Iron (impurity only)	7439-89-6
	0	0.000196g max	Aluminium (impurity only)	7429-90-5
	0	0.000196g max	Silicon (impurity only)	7440-21-3
	0	0.000492g max	Other Impurities	
	0.00146	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0225 * XX) + 0.0885	10%	30% Glass-Filled PPS	
Containing:	(0.0158 * XX) + 0.062	10%	PPS	26125-40-6
	(0.00675 * XX) + 0.0266	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
Pick & Place Cap - Phosphor Bronze	0.0993	2%	Copper	7440-50-8
	0.00524	1%	Tin	7440-31-5
	0.000215	0.3%	Phosphorus	7723-14-0
	0	0.00021g max	Zinc (impurity only)	7440-66-6
	0	0.00021g max	Nickel (impurity only)	7440-02-0
	0	0.000105g max	Iron (impurity only)	7439-89-6
	0	0.000021g max	Lead (impurity only)	7439-92-1
	0	0.00021g max	Other Impurities	

Material Declaration for M80-828XXXXP

Product Information	
Part Number:	M80-828XX42P
Part Description:	2mm pitch Vert Datamate
Part Weight (g):	(0.0368 * XX) + 0.205

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0132 * XX	2%	Copper	7440-50-8
	0.000696 * XX	1%	Tin	7440-31-5
	0.000026 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000042 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000014 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000007 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.00007 * XX)g max	Other Impurities	
	0.000066 * XX	5%	Gold	7440-57-5
	0.000131 * XX	5%	Tin	7440-31-5
	0.000147 * XX	10%	Nickel	7440-02-0
Latches - Beryllium Copper	0.0965	2%	Copper	7440-50-8
	0.00167	0.2%	Beryllium	7440-41-7
	0	0.000294g max	Nickel (impurity only)	7440-02-0
	0	0.000294g max	Cobalt (impurity only)	7440-48-4
	0	0.000196g max	Iron (impurity only)	7439-89-6
	0	0.000196g max	Aluminium (impurity only)	7429-90-5
	0	0.000196g max	Silicon (impurity only)	7440-21-3
Latches - Plating	0	0.000492g max	Other Impurities	
	0.00146	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0225 * XX) + 0.0885	10%	30% Glass-Filled PPS	
Containing:	(0.0158 * XX) + 0.062	10%	PPS	26125-40-6
	(0.00675 * XX) + 0.0266	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
Pick & Place Cap - Phosphor Bronze	0.0993	2%	Copper	7440-50-8
	0.00524	1%	Tin	7440-31-5
	0.000215	0.3%	Phosphorus	7723-14-0
	0	0.00021g max	Zinc (impurity only)	7440-66-6
	0	0.00021g max	Nickel (impurity only)	7440-02-0
	0	0.000105g max	Iron (impurity only)	7439-89-6
	0	0.000021g max	Lead (impurity only)	7439-92-1
	0	0.00021g max	Other Impurities	

Material Declaration for M80-828XXXXP

Product Information	
Part Number:	M80-828XX45P
Part Description:	2mm pitch Vert Datamate
Part Weight (g):	(0.0368 * XX) + 0.205

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0132 * XX	2%	Copper	7440-50-8
	0.000696 * XX	1%	Tin	7440-31-5
	0.000026 * XX	0.3%	Phosphorus	7723-14-0
	0	(0.000042 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000014 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000007 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.00007 * XX)g max	Other Impurities	
	0.000188 * XX	5%	Gold	7440-57-5
	0.000147 * XX	10%	Nickel	7440-02-0
Latches - Beryllium Copper	0.0965	2%	Copper	7440-50-8
	0.00167	0.2%	Beryllium	7440-41-7
	0	0.000294g max	Nickel (impurity only)	7440-02-0
	0	0.000294g max	Cobalt (impurity only)	7440-48-4
	0	0.000196g max	Iron (impurity only)	7439-89-6
	0	0.000196g max	Aluminium (impurity only)	7429-90-5
	0	0.000196g max	Silicon (impurity only)	7440-21-3
	0	0.000492g max	Other Impurities	
	0.00146	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0225 * XX) + 0.0885	10%	30% Glass-Filled PPS	
Containing:	(0.0158 * XX) + 0.062	10%	PPS	26125-40-6
	(0.00675 * XX) + 0.0266	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
Pick & Place Cap - Phosphor Bronze	0.0993	2%	Copper	7440-50-8
	0.00524	1%	Tin	7440-31-5
	0.000215	0.3%	Phosphorus	7723-14-0
	0	0.00021g max	Zinc (impurity only)	7440-66-6
	0	0.00021g max	Nickel (impurity only)	7440-02-0
	0	0.000105g max	Iron (impurity only)	7439-89-6
	0	0.000021g max	Lead (impurity only)	7439-92-1
	0	0.00021g max	Other Impurities	

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET
 Compliance Consultant
 ComplianceTeam@harwin.co.uk

On behalf of:

