

Material Composition for F10-101XXX45R

Product Information	
Part Number:	F10-101XXX45R
Part Description:	0.5mm Pitch Conn.
Part Weight (g):	(0.0184 * XXX) + 0.439

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold flash over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Signal Contact - Copper Alloy	0.00382 * XXX	5%	Copper	7440-50-8
	0.000131 * XXX	1%	Nickel	7440-02-0
	0.00007 * XXX	0.5%	Magnesium	7439-95-4
	0.000029 * XXX	0.5%	Silicon	7440-21-3
	0.000253 * XXX	10%	Nickel	7440-02-0
Signal Contact - Plating	0.000253 * XXX	10%	Gold	7440-57-5
Solder Clips - Brass	0.0165	5%	Copper	7440-50-8
	0.0085	1%	Zinc	7440-66-6
Solder Clips - Plating	0.0025	10%	Nickel	7440-02-0
	0.0025	10%	Tin	7440-31-5
Moulding (total weight)	(0.0138 * XXX) + 0.409	6%	33% GF LCP	
Containing:	(0.00897 * XXX) + 0.135	6%	Liquid Crystal Polymer	147310-94-9
	(0.00457 * XXX) + 0.135	6%	Glass Fibre	65997-17-3
	(0.000124 * XXX) + 0.00368	6%	Carbon Black	1333-86-4
	(0.000138 * XXX) + 0.00409	6%	Other	-

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.com

On behalf of:

