

Material Composition for F30-101XXX45R

Product Information	
Part Number:	F30-101XXX45R
Part Description:	0.8mm Pitch Conn.
Part Weight (g):	(0.0164 * XXX) + 0.167

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold flash over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	0.00404 * XXX	5%	Copper	7440-50-8
	0.00045 * XXX	1%	Tin	7440-31-5
	0.000007 * XXX	0.5%	Phosphorus	7723-14-0
Contact - Plating	0.000042 * XXX	10%	Nickel	7440-02-0
	0.000042 * XXX	10%	Gold	7440-57-5
Solder Clips - Brass	0.025	5%	Copper	7440-50-8
	0.0129	1%	Zinc	7440-66-6
Solder Clips - Plating	0.0026	10%	Nickel	7440-02-0
	0.0026	10%	Tin	7440-31-5
Moulding (total weight)	(0.0118 * XXX) + 0.124	6%	33% GF LCP	
Containing:	(0.00767 * XXX) + 0.0806	6%	Liquid Crystal Polymer	147310-94-9
	(0.00391 * XXX) + 0.041	6%	Glass Fibre	65997-17-3
	(0.000106 * XXX) + 0.00112	6%	Carbon Black	1333-86-4
	(0.000118 * XXX) + 0.00124	6%	Other	-

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET
 Compliance Specialist
 ComplianceTeam@harwin.com

On behalf of:

