

Material Declaration for M80-263F104-04-00

Product Information	
Part Number:	M80-263F104-04-00
Part Description:	Datamate Mix-Tek Female cable
Part Weight (g):	1.361

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Jackscrew Circlips - Stainless Steel	0.0164	10%	Iron	7439-89-6
	0.0033	4%	Chromium (Metallic)	7440-47-3
	0.0002	4%	Nickel	7440-02-0
	0.000078	0.8%	Copper	7440-50-8
	0.000004	0.5%	Sulphur	7704-34-9
	0	0.000078g max	Carbon (impurity only)	7440-44-0
	0	0.0002g max	Silicon (impurity only)	7440-21-3
	0	0.0003g max	Manganese (impurity only)	7439-96-5
	0	0.000008g max	Phosphorus (impurity only)	7723-14-0
	0	0.00021g max	Molybdenum (impurity only)	7439-98-7
Jackscrew Bolts - Stainless Steel	0	0.00004g max	Niobium (impurity only)	7440-03-1
	0	0.00002g max	Titanium (impurity only)	7440-32-6
	0.4	10%	Iron	7439-89-6
	0.099	4%	Chromium (Metallic)	7440-47-3
	0.0495	4%	Nickel	7440-02-0
	0.00385	0.8%	Copper	7440-50-8
	0.00137	0.5%	Sulphur	7704-34-9
	0	0.00066g max	Carbon (impurity only)	7440-44-0
	0	0.0055g max	Silicon (impurity only)	7440-21-3
	0	0.011g max	Manganese (impurity only)	7439-96-5
Moulding (total weight)	0	0.00033g max	Phosphorus (impurity only)	7723-14-0
	0	0.0055g max	Molybdenum (impurity only)	7439-98-7
	0	0.0011g max	Niobium (impurity only)	7440-03-1
	0	0.00055g max	Titanium (impurity only)	7440-32-6
	0.788	10%	30% Glass-Filled PPS	
	Containing:	0.551	10%	PPS
Does not contain:	0.236	10%	30% Glass Fibre	65997-17-3
			Antimony	
Other Brominated Flame Retardants				

Prepared by:



Martin J Perry, BSc(Eng) MSc CEng MIET
 Compliance Consultant
 complianceteam@harwin.co.uk

On behalf of:

