

Material Declaration for M80-335

Product Information	
Part Number:	M80-335
Part Description:	Male Straight Power Contact
Part Weight (g):	0.373

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Beryllium Copper	0.336	2%	Copper	7440-50-8
	0.00653	1%	Beryllium	7440-41-7
	0.00138	2%	Lead	7439-92-1
	0	0.00103g max	Cobalt (impurity only)	7440-48-4
	0	0.000687g max	Iron (impurity only)	7439-89-6
	0	0.000687g max	Aluminium (impurity only)	7429-90-5
Contact Shell - Plating	0	0.000687g max	Silicon (impurity only)	7440-21-3
	0	0.00103g max	Nickel (impurity only)	7440-02-0
	0	0.00172g max	Other Impurities	
	0.00262	10%	Nickel	7440-02-0
	0.00106	30%	Gold	7440-57-5
Contact Sleeve - Beryllium Copper	0.0248	2%	Copper	7440-50-8
	0.000101	0.4%	Beryllium	7440-41-7
	0.000456	0.8%	Nickel	7440-02-0
	0	0.000076g max	Cobalt (impurity only)	7440-48-4
	0	0.000025g max	Iron (impurity only)	7439-89-6
	0	0.000127g max	Other Impurities	
Contact Sleeve - Plating	0.000429	10%	Nickel	7440-02-0

Prepared by:

M. J. Perry

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

HARWIN